

CLEAN VERSION OF CLAIMS WITH AMENDMENTS

What is claimed as being new and desired to be protected by  
LETTERS PATENT of the United States is as follows:

5m  
C1  
1. A sure grip screwdriver system for allowing a user to  
screw and unscrew threaded fasteners in a convenient and  
efficient manner comprising, in combination:

B1  
a shaft fabricated of a rigid metallic material in a  
cylindrical configuration with an axis and having a handle end  
and a working end, the shaft having a working inner portion  
adjacent to the handle end and a working outer portion adjacent  
to the working end and with a flat cut face on the outermost  
extent of the working end perpendicular to the axis of the shaft,  
the working outer portion having a generally cube-shaped  
configuration with a square cross section and an axial length of  
a first smaller size adjacent to the face, the working inner  
portion having a generally cube-shaped configuration with a  
square cross section and an axial length of a second larger size  
adjacent to the working outer portion, with a bevel adjacent to  
the working inner portion remote from the face;

a screwdriver handle having a shaft end and a gripping  
surface end, the shaft end having a generally cylindrical recess  
to securely receive and retain in one position the handle end of  
the shaft and with the gripping surface end having a plurality of

Sub  
C1

axial indentations to facilitate the user's grip of the system; and

a threaded fastener having a threaded portion and a head portion, the threaded portion having threads for coupling to a recipient surface upon rotation and with the head portion having a cylindrical configuration with a central stepped recess, the stepped recess having a cube-shaped interior reception area and an exterior cube-shaped reception area with the interior reception area being smaller to snugly receive the working outer portion of the shaft and with the exterior reception area being larger to snugly receive the working inner portion of the shaft and alternatively, wherein the threaded fastener is of a smaller size, the working outer portion is snugly receivable by the working outer portion and, alternatively, wherein the working portions are of a larger size, the working outer portion is snugly receivable by the working outer portion.

B1

2. A flat ended, double cube shaped tipped, screwdriver system comprising:

a shaft having a handle end and a working end, the shaft having a working inner portion adjacent to the handle end and a working outer portion adjacent to the working end, the working outer portion having a generally cube-shaped configuration of a first smaller size with a flat outermost tip being perpendicular to the shaft, the working inner portion having a generally cube-shaped configuration of a second larger size; [and]

Sub  
C1  
a shaft support with a recess at one end to receive the handle end of the shaft; and

B1  
concl  
a threaded fastener having a threaded portion and a head portion, the head portion having a cylindrical configuration with a central stepped recess, the stepped recess having a cube-shaped interior reception area with a flat innermost portion and an exterior cube-shaped reception area with the interior reception area being smaller to snugly receive the working outer portion of the shaft and the flat innermost portion allowing a positive alignment of the fastener and the working tip and with the exterior reception area being larger to snugly receive the working inner portion of the shaft.

3. (Canceled)

4. A flat ended, double cube shaped tipped, screwdriver system comprising:

B2  
a shaft having a handle end and a working end, the shaft having a working inner portion adjacent to the handle end and a working outer portion adjacent to the working end, the working outer portion having a generally cube-shaped configuration of a first smaller size with a flat outermost tip being perpendicular to the shaft, the working inner portion having a generally cube-shaped configuration of a second larger size, the shaft having a receptacle to accommodate the interchangeability of a plurality

32  
cont

of different working tips with the plurality of said different working tips having different sized working portions; and  
a shaft support with a recess at one end to receive the handle end of the shaft.

5. (Canceled)

6. A flat ended, double cube shaped tipped, screwdriver system comprising:

B3

a shaft having a handle end and a working end, the shaft having a working inner portion adjacent to the handle end and a working outer portion adjacent to the working end, the working outer portion having a generally cube-shaped configuration of a first smaller size with a flat outermost tip being perpendicular to the shaft, the working inner portion having a generally cube-shaped configuration of a second larger size, the shaft being part of a kit comprising a plurality of shafts, with each of the shafts having different sized working portions with each of the tips of the working portions having a flat outer most surface being perpendicular to the shaft, and wherein the shaft support is a power tool; and

a shaft support with a recess at one end to receive the handle end of the shaft.